



1 DOOR MATERIAL - $\frac{3}{4}$ " thick Superior Grade MDF panels available in a variety of 3D Laminate colors and finishes. Doors are also available in a $\frac{3}{4}$ " Acrylic, Solid Maple and Aluminum Framed Glass. All doors and false fronts are $\frac{3}{4}$ " thick.

2 END PANEL - All end panels are $\frac{5}{8}$ " thick Thermally Fused Melamine (TFM), providing scratch, moisture and stain resistance.

3 TOP/BOTTOM PANELS - All tops and bottoms are $\frac{5}{8}$ " thick TFM, providing scratch, moisture and stain resistance. Tops and bottoms are doweled into cabinet sides. Top corners in sink base are secured with 3"x3" corner braces.

4 BACK PANEL - All wall backs are $\frac{5}{8}$ " thick TFM, while base backs are $\frac{1}{4}$ " thick TFM with an additional $\frac{5}{8}$ " thick TFM rear stretcher, providing scratch, moisture and stain resistance. Wall backs are rabbeted into top, bottom and sides. Wall cabinets can be fastened to the wall from anywhere on the back which helps keep the cabinet true and square.

5 SHELVES - All shelves are $\frac{5}{8}$ " thick TFM, providing scratch, moisture and stain resistance. Wall cabinet shelves are full depth, standard base cabinets are half depth. All shelves are adjustable.

6 TOE KICK - Matching $\frac{1}{4}$ " thick TFM, providing scratch, moisture and stain resistance.



DRAWERS - All drawer backs and bottoms are $\frac{5}{8}$ " thick TFM providing scratch, moisture and stain resistance. Metal sides with soft-close mechanism, a vertical adjustment steel front coupler on drawer front and Lifetime Warranty.

HINGES - Standard integrated soft-close hinge with a 110° opening. All metal or steel hinges, nickel plated. 6-way adjustable with Lifetime Warranty.

MATERIAL

- Material for cabinet components is regionally sourced.
- Recycled and/or recovered wood material.
- Cabinets are produced using CARB II ATCM compliance with the availability of Ultra Low Emission Formaldehyde (ULEF).



Manufactured & Distributed By:

